

Model Number		TM09HFDI	TM12HFDI	TM18HFDI	TM24HFDI
Type		SLIM DUCT			
<b>SYSTEM PERFORMANCE</b>					
Voltage/Phase/Hertz		208-230V/1/60Hz	208-230V/1/60Hz	208-230V/1/60Hz	208-230V/1/60Hz
Cooling Capacity	Btu/h	8,500	11,900	15,300	23,800
Heating Capacity	Btu/h	9,500	13,100	18,700	27,400
Airflow (min/max)	CFM	147/265	177/324	294/412	324/589
Sounds Level (min/max)	dB(A)	31/37	32/39	33/41	34/42
Dehumification	pt/hr	1.7	3.0	3.8	5.3
<b>DIMENSIONS</b>					
Unit Dimensions (WxHxD)	in	27.6x7.9x24.2	27.6x7.9x24.2	35.4x7.9x24.2	43.3x7.9x24.2
Package Dimensions (LxWxH)	in	35.2x29.3x12.0	35.2x29.3x12.0	44.2x29.3x12.0	52.1x29.3x12.0
Weight (Net/Gross)	lbs	47/60	51/64	60/79	68/90
<b>INSTALLATION</b>					
Line Connection Size (Liquid - Gas/Suction)	in	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	3/8 - 5/8