## CANNON LOAD BANKS, INC.

PALMETTO, GA. 30268

PHONE 770-463-0504

## **MODEL L-67**

**PORTABLE LOAD BANK** 

THE L-67 LOAD BANK is designed to provide a temporary load for field servicing and testing 120/240 volt single phase or 120/208 three phase 60HZ generators and inverters. This load bank is air cooled and completely self contained. The unit can load three phase 208VAC up to 70KW and 240VAC single phase up to 46KW.

## **MODEL L-67 DIMENSIONS**

Length	22"
Width	8"
Height	21"
Weight	55 lbs





## **FEATURES**

- Load steps: 1,2,2, 5, 10, 20, 30KW @208VAC Three Phase
- Load steps: .66,1.32,1.32, 3.3, 6.6, 13.3, 19.8KW @240VAC single phase
- Load steps: .33,.66,.66, 1.7, 3.3, 6.6, 9.9KW @120VAC single phase
- Plug test pins for connecting test leads
- Receptacle for ten foot cable(included with load bank)
- Meters: 0-150VDC voltmeter, 0-250A amp meter, 55-65HZ frequency meter
- Power indicator lights
- Thermal protection
- Carrying case
- Folding handle

WEBSITE: WWW.CANNONLOADBANKS.COM