

JTR-MF7923/BHA Series

Bottom Hemming Automat



TIMESAVING			
TIME MANUEL METHOD	TIME AUTOMATED METHOD	TIMESAVING PERCENT	
17 SEC	9.6 SEC	44%	
<small>*Time-saving is calculated for this machine is with 1 operator 2 machines</small>			
ADDITIONAL BENEFITS			
ONE OPERATOR TWO MACHINES	STANDARD QUALITY	EASY OPERATION	SPEED
✓	✓	✓	✓

Highlights

- Able to sew t-shirt bottom in tubular form with or without side seam
- An operator can operate 2 or 3 machines
- Automatic step motor controlled size change between different sizes via touchscreen
- Size tolerance system adapts machine for measurement differences up to 1 cm for each size
- 2 or 3 needle coverseam stitch with perfect overlap sewing stitch at the end of operation
- Minimum fabric trimming waste due to servo motor controlled left hand knife system
- Photocell controlled bottom edge guiding system
- Automatic stacker

HEMMING SIZE	NEEDLE GAUGE				
	BOTTOM COVER	BOTTOM COVER	BOTTOM COVER	TOP COVER	TOP COVER
 Hemming Size 16-28 mm	 2 NEEDLES 4.8 mm	 3 NEEDLES 5.6 mm	 3 NEEDLES 6.4 mm	 3 NEEDLES 5.6 mm	 3 NEEDLES 6.4 mm
	 2 NEEDLES 4.8 mm	 2 NEEDLES 5.6 mm	 2 NEEDLES 6.4 mm	 2 NEEDLES 5.6 mm	 2 NEEDLES 6.4 mm
	 2 NEEDLES 2.8 mm	 2 NEEDLES 3.2 mm	 2 NEEDLES 2.8 mm	 2 NEEDLES 2.8 mm	 2 NEEDLES 3.2 mm

TECHNICAL SPECIFICATION


Machine Head (Standard)	MF7923H23
Motor	Efka AB221 Direct Drive Servo
Max. Sewing Speed	5.500 rpm
Max. Sewing Speed in Operation	4.500 rpm
Capacity	2.400 - 3.000 t-shirts / 9 hours (1 operator 1 machine) 4.500 - 5.000 t-shirts / 9 hours (1 operator 2 machines)
Daily Piece Counter	Available
Thread Breakage Detection	Available
Max. - Min. Bottom Hem Length	35 cm - 78 cm
Max. - Min. Bottom Hem Width	Shipping value: 20 mm By adjustment: 16 - 22 mm&up to 28 mm (special order)
Min. - Max. Stitch Length	2 mm - 3.5 mm
Needle Type	GB - UY128 - #11
Needle Gauge	4.8 mm - 5.6 mm - 6.4 mm
Power Requirement / Power Consumption	Single-phase 220V-240V 50Hz / 1.200VA
Compressed Air / Air Consumption	6 Bar / 23 L/min.

JTR-MF7923/BHA Series



Bottom Hemming Automat

WHEN YOU PLACE ORDERS

Please note when placing orders, that the model name should be written as follows.



SHIPMENT DETAILS	
Machine net weight	198 kg
Machine / Stacking unit gross weight (Including palette and package)	210 kg / 70 kg
Machine net dimensions:	
Width	110 cm
Length	240 cm
Height	170 cm
Package dimensions (Machine):	
Width	120 cm
Length	140 cm
Height	160 cm
Package dimensions (Stacking Unit):	
Width	70 cm
Length	110 cm
Height	130 cm
HS code	8452.21.00.00.00



JUKI
JUKI CORPORATION
 SEWING MACHINERY & SYSTEMS BUSINESS UNIT

2-11-1, TSURUMAKI, TAMA-SHI,
 TOKYO 206-8551, JAPAN
 PHONE: (81) 42-357-2370
 FAX: (81) 42-357-2274
<https://www.juki.co.jp/en>

* Specifications and appearance are subject to change without prior notice for improvement.
 * Read the instruction manual before putting the machine into service to ensure safety.
 * This catalogue prints with environment-friendly soyink on recycle paper.
 * Paper from responsible sources FSC™ C001712